

Please tick here if quote request only






### Contact details

Company name \_\_\_\_\_  
 Delivery address \_\_\_\_\_  
 \_\_\_\_\_ Postcode \_\_\_\_\_  
 Reference \_\_\_\_\_  
 Requested delivery date \_\_\_\_\_  
 Telephone \_\_\_\_\_  
 Fax \_\_\_\_\_  
 Email \_\_\_\_\_  
 Ordered by \_\_\_\_\_

### Window specification

Window colour  White (standard)  
 Other (specify) \_\_\_\_\_  
 Outerframe depth  133mm  146mm (standard)  
 Deep bottom rail  Yes  No (standard)  
 Gasket colour  White  Black (standard)  
 Hardware  White (standard)  Gold  
 Chrome  Pewter  
 Other (specify) \_\_\_\_\_  
 Key locking?  Yes (standard)  No

Please ensure windows will comply with all relevant planning requirements, Building Regulations and FENSA guidelines, etc.  
 If in doubt please contact the sales office for advice.

No. of windows					
Reference					
Total width		mm	mm	mm	mm
Total height		mm	mm	mm	mm
Transom drop					
Fire Escape?	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Opening restrictor	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Decorative horns	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Horn type	<input type="checkbox"/> Cont <input type="checkbox"/> Plant	<input type="checkbox"/> Cont <input type="checkbox"/> Plant	<input type="checkbox"/> Cont <input type="checkbox"/> Plant	<input type="checkbox"/> Cont <input type="checkbox"/> Plant	<input type="checkbox"/> Cont <input type="checkbox"/> Plant
Tilt facility	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F
Vent required	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Vent Location	<input type="checkbox"/> Trickle <input type="checkbox"/> Add-on	<input type="checkbox"/> Trickle <input type="checkbox"/> Add-on	<input type="checkbox"/> Trickle <input type="checkbox"/> Add-on	<input type="checkbox"/> Trickle <input type="checkbox"/> Add-on	<input type="checkbox"/> Trickle <input type="checkbox"/> Add-on
Spacer bar colour					
W.E.R. Rating	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Georgian bar type	<input type="checkbox"/> A <input type="checkbox"/> GIN <input type="checkbox"/> NA	<input type="checkbox"/> A <input type="checkbox"/> GIN <input type="checkbox"/> NA	<input type="checkbox"/> A <input type="checkbox"/> GIN <input type="checkbox"/> NA	<input type="checkbox"/> A <input type="checkbox"/> GIN <input type="checkbox"/> NA	<input type="checkbox"/> A <input type="checkbox"/> GIN <input type="checkbox"/> NA
Outside sketch Please sketch in any Georgian bar or glass requirements T = Toughened Glass L = Laminated O = Obscure (Please provide Pattern) Obscure Pattern =					
Extra cill (welded?)	@ mm	@ mm	@ mm	@ mm	@ mm
Coupler	mm	mm	mm	mm	mm
Frame extension	@ mm	@ mm	@ mm	@ mm	@ mm
Bay assembly	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135
Fixing lugs	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No

Additional requirements:

**10 Year  
Guarantee**



### Header Details

**Quote Request** - please tick this box if you are enquiring about prices only - **leave blank for orders**

**Your Details** - please provide us with complete and accurate information to allow rapid order processing - including full delivery address, especially if different from your office/factory address. Request the date windows are required (Std. lead time is 2-3 weeks) we will confirm delivery date by fax. Include your contact details (Placed By) in case we need to clarify anything on your order, and please give orders a clear order reference - preferably with your purchase order number for maximum traceability and quick easy invoicing.

### Window Details

NB: Please order windows in same room/elevation together to help us match specification/style. Some windows may require large/large sash combination due to size - standard is large/small sashes.

- 1 Outerframe Depth** - Our Elegance VS is available in two frame depths, please order which best suits your reveal depth requirements. The 146mm frame is ovolo moulded on both the internal and external faces, the 133mm is flat internally. The integral cill is always 146mm.
- 2 Deep Bottom Rail** - A mechanically jointed aesthetic optional extra to replicate traditional sightlines - bottom sash base rail is 105mm in height.
- 3 Gasket Colour** - Elegance VS have lowline gaskets as standard - please choose white or black gasket colour (white gasket on plain white only).
- 4 Hardware** - KAT sash windows are manufactured with a full suite of bespoke matching window hardware, with white fitted as standard. We also have available hardware finished in gold, bright chrome, antique pewter or black. Other finishes are available on request subject to extended lead times and/or surcharge, please specify.
- 5 Key Locking** - For extra security key locking cams are fitted as standard - thumb turn/non-locking cams are available, if required tick 'No'.
- 6 Number of Windows** - If you wish to order multiple windows of identical size and specification state required quantity here.
- 7 Reference** - This offers the opportunity to reference your windows individually for easy identification on site (Lounge, bedroom, etc.) and your reference will be displayed on frame labels.
- 8 Total Width** - Please state the total overall finished window width including any extras or frame extenders, etc.
- 9 Total Height** - Please state the total overall finished window height including any extra cills or frame extenders, etc.
- 10 Transom Drop** - Please state the dimension from the top of the outerframe to the central meeting point of the sashes, if left blank standard is half the height of the window - but we can cater for most requirements (1/3rd - 2/3rds or 2/5ths - 3/5ths etc.).
- 11 Fire Escape?** - If the window needs to meet Part B fire egress requirements let us know! Please note minimum sizes apply (KAT will confirm compliance) and where this option is selected hardware configuration should be checked with local planning department. KAT UK have special side hinged Fire Egress windows available (at an extra charge) to allow smaller frames to comply with Building Regulations.
- 12 Opening Restrictors** - Primarily a child safety feature, these bespoke fixtures limit the sash opening - available in white, gold, bright chrome and antique pewter only.
- 13 Decorative Horns** - Aesthetic optional extras available to mimic authentic features - fitted to the bottom of the top sash. KAT Elegance sash window are available with a choice of continuous 'run through' sash horns for a traditional look - alternatively a standard 'plant on' horn is also available.
- 14 Tilt Facility** - 'No' = Standard sashes will slide up and down only, 'Yes' = optional 'easy clean' tilt facility available to facilitate cleaning from inside + extra ventilation etc. - 2 tilt restrictor arms are fitted to all tilting sashes, 'F' = a totally fixed window (both sashes).
- 15 Vent Required** - 2200mm & 4400mm E/A night vents are available fitted through either the head of the top sash or alternatively through a 30mm or 50mm add-on to the head of the outerframe (please specify which option you require, 'Sash' or 'ADD-ON').
- 16 Spacer Bar Colour** - KAT VS are supplied with white spacer bars as standard, other colours are available on request. Warmedge/Thermal spacer bars are only available in white, black or grey.
- 17 W.E.R. Rating** - Select the BFRC approved window energy rating required. All frames with standard 4-16-4 glass configuration will be supplied 'C' rated as standard.
- 18 Georgian Bar type** - Authentic = 'A' for face planted PVCu bars (inside + outside unit), Glazed In = 'GIN' for 18mm or 25mm glazed in bars (inside unit only) please specify thickness required, or None = 'N/A'. Please sketch Georgian layouts in the window diagrams provided.
- 19 Outside Sketch** - All KAT VS are fully glazed with 4-16-4 clear Planitherm Total + low 'e' glass as standard, for any additional glazing requirements e.g. toughened/Laminated mark the window drawings with 'T' or 'L' as applicable, for obscure glass 'O' please confirm desired pattern.
- 20 Extra Cill** - 85mm, 120mm, 160mm & 200mm cills available to go under the frame, 160/200mm can be welded for bays. Specify which cill and overall size, if cill horns/over length cills are required.
- 21 Coupler** - A 2mm PVCu 'H' section trim is available for fixing multiple frames together, they also require screw fixing. As standard, Elegance coupled windows will be supplied separately to be joined on site, for ease of installation.
- 22 Frame Extension** - 15mm, 30mm & 50mm add-ons available to build up frame - 55mm depth, ideal for check reveals. Specify which add-on and required size/quantity (2 no. required to build up front and back).
- 23 Bay Assembly** - A non-structural baypole is available in either 90°, 120° or 135° fixed angles. A variable bay pole assembly will be supplied with foiled products. Please sketch bays on additional sheets.
- 24 Fixing Lugs** - To assist with quick, easy, high quality installation stainless steel fixing lugs are available, 'yes' = 6 supplied per window.

### Additional Requirements:

Please include details of any special requirements in space provided or on supplementary sheets, e.g. drawings of bays, etc. If your sash window needs to comply with any special regulations, i.e. B.B.A. or BS7950 or if you wish for a particular W.E.R. rating please let us know, we will try to oblige.

If you are planning to install KAT sash windows in a severe weather facing location, please contact the sales office for advice.

### Bays, Welded Cills and Arched Windows

A separate order form is available for arched windows, please enquire - please also sketch any bay layouts on additional sheets.

NB: Please give finished internal facet sizes and required. Angles for any bay window assemblies.

