



KAT Classic Box Sash Windows

Order form
June 2016

☐ Enquiry please quote ☐ Order please process

Contact details

Company name _____

Delivery address _____

_____ Postcode _____

Reference _____

Requested delivery date _____

Telephone _____

Fax _____

Email _____

Ordered by _____

Window specification

Window colour ☐ White ☐ White foil both sides

☐ Cream foil both sides ☐ Oak foil both sides

☐ Rosewood on both sides ☐ Oak on white

☐ Rosewood on white ☐ Other (specify) _____

Deep bottom rail ☐ No ☐ Yes

Cill depth ☐ 150mm ☐ 210mm

Hardware ☐ White (standard) ☐ Satin ☐ Chrome

☐ Antique gold ☐ Pewter

☐ Window has to comply with Document Q of the Building Regulations
(additional costs apply for the SBD specification product)

No. of windows					
Reference					
Total width	mm	mm	mm	mm	mm
Total height	mm	mm	mm	mm	mm
Transom drop					
Fire Escape	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Opening restrictor	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Decorative horns	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Horn type	<input type="checkbox"/> Cont <input type="checkbox"/> Plant	<input type="checkbox"/> Cont <input type="checkbox"/> Plant	<input type="checkbox"/> Cont <input type="checkbox"/> Plant	<input type="checkbox"/> Cont <input type="checkbox"/> Plant	<input type="checkbox"/> Cont <input type="checkbox"/> Plant
Tilt facility	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F
Vent required	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Vent location	<input type="checkbox"/> Top sash only	<input type="checkbox"/> Top sash only	<input type="checkbox"/> Top sash only	<input type="checkbox"/> Top sash only	<input type="checkbox"/> Top sash only
Spacer bar colour					
W.E.R. Rating	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Georgian bar type	<input type="checkbox"/> A <input type="checkbox"/> GIN	<input type="checkbox"/> A <input type="checkbox"/> GIN	<input type="checkbox"/> A <input type="checkbox"/> GIN	<input type="checkbox"/> A <input type="checkbox"/> GIN	<input type="checkbox"/> A <input type="checkbox"/> GIN
Georgian bar width	<input type="checkbox"/> Slim <input type="checkbox"/> Wide	<input type="checkbox"/> Slim <input type="checkbox"/> Wide	<input type="checkbox"/> Slim <input type="checkbox"/> Wide	<input type="checkbox"/> Slim <input type="checkbox"/> Wide	<input type="checkbox"/> Slim <input type="checkbox"/> Wide
Window design Please sketch in any Georgian bar or glass requirements T = Toughened Glass L = Laminated O = Obscure (Please provide Pattern) Obscure Pattern =					
Coupler	mm	mm	mm	mm	mm
Extra cill (welded)	@ mm	@ mm	@ mm	@ mm	@ mm
Frame extension	@ mm	@ mm	@ mm	@ mm	@ mm
Bay pole	<input type="checkbox"/> 90 <input type="checkbox"/> Variable	<input type="checkbox"/> 90 <input type="checkbox"/> Variable	<input type="checkbox"/> 90 <input type="checkbox"/> Variable	<input type="checkbox"/> 90 <input type="checkbox"/> Variable	<input type="checkbox"/> 90 <input type="checkbox"/> Variable
Fixing lugs	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No

Additional requirements:

Header Details

Quote Request - please tick this box if you are enquiring about prices only - **leave blank for orders**

Your Details - please provide us with complete and accurate information to allow rapid order processing - including full delivery address, especially if different from your office/factory address.

Request the date your windows are required (standard lead time is 2-3 weeks) we will confirm delivery date by fax. Include your contact details (placed by name) in case we need to clarify anything on your order.

Please give your orders a clear 'order reference' - preferably with your purchase order no. for maximum traceability and quick easy invoicing.

Window Details

NB: Please order windows in same room/elevation together to

Help us match specification/style.

Some windows may require large/large sash combination due to size - standard is large/small sashes.

Outerframe Depth - The KAT Classic sash window is only available in one frame depth of 128mm front to back dimension.

- 1 **Window Colour** - White is standard, there is a Classic range of colours available please note required foiled/painted finish under 'other'.
- 2 **Deep Bottom Rail** - A mechanically jointed aesthetic optional extra to replicate traditional sight lines - bottom sash base rail is 90mm in height.
- 3 **Cill Size** - KAT Classic has integral cills as a base to the frame, 150mm/short is standard but 210mm/projecting is available.
- 4 **Hardware** - Standard KAT sash windows are manufactured with a full suite of matching white window hardware, we also have available hardware suites finished in bright chrome, satin, pewter and antique gold.
- 5 **Key Locking** - For extra security all catches feature allen-key locks
- 6 **Number of Windows** - If you wish to order multiple windows of identical size and specification please state required quantity here.
- 7 **Reference** - This offers the opportunity to reference your windows individually for easy identification on site (Lounge, bedroom, etc.) and your reference will be displayed on frame labels.
- 8 **Total Width** - Please state the total overall finished window width including any extras or frame extenders, etc.
- 9 **Total Height** - Please state the total overall finished window height including any cills, extras or frame extenders, etc.
- 10 **Transom Drop** - Please state the dimension from the top of the outerframe to the central meeting point of the sashes, if left blank KAT's standard is half the height of the window - but we can cater for most requirements (1/3rd - 2/3rds or 2/5ths - 3/5ths etc.).
- 11 **Fire Escape?** - If the window needs to meet Part B fire egress requirements let us know! Please note minimum sizes do apply (KAT will confirm compliance) and where this option is selected hardware configuration should be checked with local planning department. KAT UK have special side hinged Fire Egress windows available (at an extra charge) to allow smaller frames to comply with Building Regulations.
- 12 **Opening Restrictors** - Primarily a child safety feature these limit the sash opening - available in white, gold or chrome only.
- 13 **Decorative Horns** - Aesthetic optional extras available to mimic authentic features - fitted to the bottom of the top sash. KAT Classic sash windows are available with a choice of continuous 'run through' sash horns for a traditional look - alternatively a standard 'plant on' horn is also available.

- 14 **Tilt Facility** - 'No' = Standard sashes will slide up and down only, 'Yes' = optional 'easy clean' tilt facility available to facilitate cleaning from inside + extra ventilation, etc. - 2 tilt restrictor arms are fitted to all tilting sashes, 'F' = a totally fixed window (both sashes).
- 15 **Vent Required** - 2200mm and 4400mm E/A controllable night vents are available - fitted through the head of the top sash.
- 16 **Spacer Bar Colour** - KAT VS are supplied with white spacer bars as standard, gold in woodgrain, other colours are available on request. Warmedge/Thermal spacer bars are available in white, black or grey.
- 17 **W.E.R. Rating** - Select the BFRC approved window energy rating required. All frames with standard 4-16-4 glass configuration will be supplied 'C' rated as standard.
- 18 **Georgian Bar type** - Select Georgian Bar type if required, Authentic = 'A' for face planted PVCu astragal bars (inside + outside unit), Glazed In = 'Gin' for glazed in Georgian bars (inside unit only), Please sketch Georgian layouts in the diagrams provided.
- 19 **Georgian Bar Width** - Classic VS has two widths of Authentic Bar (22mm & 30mm) and two widths of Glazed In Bar (18mm or 25mm please specify if you would prefer the 'SLIM' or 'WIDE' bars after specifying which type of bar is required in the field above. Wide authentic bars are only available in plain white or oak finishes.
- 20 **Outside Sketch** - All KAT VS are fully glazed with 4-16-4 clear Planitherm Total + low 'e' glass as standard, for any additional glazing requirements e.g. toughened/laminated mark the window drawings with 'T' or 'L' as applicable, for obscure glass 'O' please confirm desired pattern.
- 21 **Coupler** - A 2mm PVCu 'H' section trim is available for fixing multiple frames together, they also require screw fixing. As standard KAT Classic coupled sash windows will be supplied on a continuous integral cill, for larger windows sashes will be removed for delivery/installation.
- 22 **Frame Extension** - a small (20mm tall x 70mm deep) or large (50mm tall x 70mm deep) add-on is available if required, an odd leg adaptor (10mm tall x 19mm deep) is also available - ideal for check reveals.
- 23 **Bay Assembly** - A non-structural variable angle bay pole is available for bays between 120° and 150° - a 90° fixed bay pole is also available.
- 24 **Fixing Lugs** - To assist with quick, easy, high quality installation stainless steel fixing lugs are available, 'Yes' = 6 supplied per window.

Additional Requirements:

Please include details of any special requirements in space provided or on supplementary sheets, e.g. drawings of bays, etc. If your sash window needs to comply with any special regulations, i.e. B.B.A. or BS7950 or if you wish for a particular W.E.R. rating please let us know, we will try to oblige.

If you are planning to install KAT sash windows in a severe weather facing location, please contact the sales office for advice.

Bays, Welded Cills and Arched Windows

A separate order form is available for arched windows, please enquire - please also sketch any bay layouts on additional sheets.

Window has to comply with Document Q of the Building Regulations (additional costs apply for the SBD specification product)

NB: please give us the finished internal facet sizes and required angles for any bay window assemblies.