



Schüco ASS70FD Bifold Doors

TRADE
Quote/Order form
June 2016

Enquiry please quote Order please process

Date _____

Contact details

Ordered by _____

Company name _____

Address _____

Postcode _____

Telephone _____

Fax _____

Email _____

Order No. _____ Your Reference _____

Delivery date requested _____

Site Contact

Contact name _____

Delivery Address _____

Postcode _____

Telephone _____

Delivery option

- Fully assembled with outer frame joints sealed with silicone
- Outer frame sealed but sashes separate
- Kit form (all items over 5000 x 2500 will be supplied in kit form)

Overall frame width (mm) _____

Overall frame height (mm) _____

Door will be fitted in:

- Sheltered location
- Exposed location

Opening direction Inward Outward

Cill requirements included in overall frame height

- 150mm
- 190mm
- No cill required

Note: Cill platform height is 25mm

Glazing

- Glazed Unglazed
- 28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer
- Touch-up paint
- Keyed Alike

Bottom track detail

- 60mm standard threshold excluding cill - weathered
- 4mm low threshold (no cill) - non weathered

Single Colour (both sides)

- White RAL 9106 gloss finish
- Grey RAL 7016 matt finish
- Black RAL 9005 matt finish
- Other RAL colour _____ (Extended lead time)

Dual Colour (Extended lead time)

Internal RAL _____

External RAL _____

1 x 5000 aluminium trickle vent through 44mm add-on (includes 44mm add on to head)

- No
- Black
- White

Drainage required Yes No

Master Handles

- Black
- Anodised silver

Intermediate handle

- Yes

Door has to comply with Document Q of the Building Regulations (additional costs apply for the SBD specification product)

Shootbolt Handle

- Locking? Yes No
- Black Anodised satin

Bead

- Square

Opening configuration - viewed from outside



Total number of sashes

Number of sashes folding left

Number of sashes folding right

Ulltion cylinder lock fitted as standard

