Enquiry please quote Order please process	Date
	Door will be fitted in:
Contact details	Sheltered location Exposed location
Ordered by	Single Coloure
Company name	Single Colours
Address	RAL 9016 Traffic White Gloss RAL 7016 Anthracite Grey Matt
Postcode	RAL 9005 Black Matt
Telephone	RAL 7035 Light Grey Matt
Fax	RAL 7015 Textured Slate Grey
Email	Dual Colours
Order No Your Reference	RAL 9005 Black Matt outside/ RAL 9016 Traffic White Gloss inside
Delivery date requested	RAL 7016 Anthracite Grey Matt outside/ RAL 9016 Traffic White Gloss inside
Site Contact	Note: For other RAL colours, please request Schuco quote
Contact name	Anodised Black 54B - longer lead time
Delivery Address Postcode	Marine Grade Finish Yes No
Telephone	(Note: Required within 5000 metres of the sea, tidal estuary or in a swimming pool or any other chemical or industrial environments)
Size	Drainage required Yes No
Small sash 87mm meeting style Large sash 107mm meeting style Depends on the size of the sash. Small sash <160kgs, large sash 160 - 200kgs	Sliding panel - internal standard. Tick box for external slider (Depends on door style)
Outerframe Outerframes are delivered in kit form. They must be assembled and sealed on site. One tube of sealant comes with each door kit.	Handles 400mm cranked brushed stainless bar handle to inside. Pentalock actuator with 4 mushroom lock with central hook, multiple keeps. Euro cylinder escutcheon
Overall frame width (mm)	Optional:
` '	Pentalock lever & escutcheon to outside
Overall frame height (mm)	400mm or 1,000mm cranked bar handle to outside to match internal
Cill requirements (25mm included in overall frame height)	to match internal
	Midrail (width 78mm)
141mm 196mm 220mm No cill required	Yes Midrail height (from base of frame)
22mm Add on to head (170769) Yes No	Night Vent (1 x 5000mm² in frame + 34mm double add on supplied)
34mm Add on to head for night vents Yes No 22mm Add on to Jambs (170769) Yes No	Night vent colours will be colour coded to the doors except RAL 7035 which will be supplied as black.
22mm Add on to Jambs (170769) Yes No	
Glazing - square bead	Configuration - viewed from outside Please indicate below: fixed panel/s and direction of travel when
Glazed Unglazed	viewed from outside.
Standard 28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer	2 pane 3 pane 4 pane
28mm 32mm 36mm	X = slider O = fixed panel
Keyed Alike	
Note: Lead time will be increased if other components ordered	
90° fixed corner post for bays only	