

Triple track Kawneer Aluminium Lift & Slide Patio Door

TRADE Quote/Order form May 2017

Enquiry please quote Order please process	Date
	Keyed Alike
Contact details	Note: Lead time will be increased if other components ordered
Ordered by	Door will be fitted in:
Company name	Sheltered location Exposed location
Address	90° corner post
Postcode	
Telephone	Single Colours
Fax	RAL 9016 Traffic White Gloss
Email	RAL 7016 Anthracite Grey Matt RAL 9005 Black Matt
Order No Your Reference	RAL 7035 Light Grey Matt
Delivery date requested	RAL 7015 Textured Slate Grey
	Dual Colours
Site Contact	RAL 9005 Black Matt outside/ RAL 9016 Traffic White Gloss inside
Contact name	RAL 7016 Anthracite Grey Matt outside/ RAL 9016 Traffic White
Delivery Address	Gloss inside
Postcode	Note: For other RAL colours, please request Schuco quote
Telephone	Anodised Black 54B
Size	Marine Grade Finish Yes No
Small sash 87mm meeting style	
Large sash 107mm meeting style	(Note: Required within 5000 metres of the sea, tidal estuary or in a swimming pool or any other chemical or industrial environments)
Outsetsess	Drainage required Yes No
Outerframe Outerframes are delivered in kit form. They must be assembled and sealed on site. Two tubes of sealant come with each door kit.	Cliding panel internal standard Tick how for outernal alider
and Sealed on Site. Two tubes of Sealant come with each door kit.	Sliding panel - internal standard. Tick box for external slider
Overall frame width (mm)	Handles - Brushed stainless bar handle inside and out
Overall frame height (mm)	Midrail (width 73mm)
	Yes Midrail height (from base of frame)
Cill requirements (25mm included in overall frame height)	
194mm 249mm 273mm No cill required	Night Vent (1 x 5000mm ² in frame + 34mm double add on supplied)
	Black White Grey
22mm Add on to head Yes No	Bead
34mm Add on to head for night vents Yes No	28mm 32mm 36mm
22mm Add on to Jambs Yes No	Configuration - viewed from outside Please indicate below: fixed panel/s and direction of travel when
Glazing - square bead	viewed from outside.
Glazed Unglazed	X = slider O = fixed panel
28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer	
32mm 36mm	
Door has to comply with Document Q of the Building Regulations (additional costs apply for the PAS 24:2016 specification product)	