

Enquiry please quote Order please process

Date _____

Contact details

Ordered by _____

Company name _____

Address _____

_____ Postcode _____

Telephone _____

Fax _____

Email _____

Order No. _____ Your Reference _____

Delivery date requested _____

Site Contact

Contact name _____

Delivery Address _____

_____ Postcode _____

Telephone _____

Opening direction Inward Outward

Please indicate door configuration **VIEWED FROM OUTSIDE. Arrowhead/s to indicate hinge position.**

Glazing

Glazed

Unglazed

28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer

Chamfered bead

Overall frame width (mm) _____

Overall frame height (mm) _____

Door has to comply with Document Q of the Building Regulations (additional costs apply for the PAS 24 specification product). Please note, not available for French Doors

Hinged on Left Right

Keyed Alike Yes

Fixtures & fittings

- Frame extension 20mm to head
- Frame extension 20mm to base
- Frame extension 20mm to both jambs

Bottom track detail

- 45mm standard threshold - weathered
- 15mm low threshold - non weathered
not recommended for exposed locations

Single Colours

- RAL 9016 Traffic White Gloss
- RAL 7016 Anthracite Grey Matt
- RAL 9005 Black Matt
- RAL 7035 Light Grey Matt
- RAL 7015 Textured Slate Grey

Dual Colours

- 9005 Black Matt outside / 9016 Traffic White Gloss inside
- 7016 Anthracite Grey Matt outside / 9016 Traffic White Gloss inside

Note: For other RAL colours, please request Schüco quote

Anodised Black 54B

Marine grade finish Yes No

Note: Required within 5000 metres of the sea, tidal estuary or in a swimming pool or any other chemical or industrial environments)

1 x 5000 aluminium trickle vent through frame
 (includes 34mm add on to head)

- No Black White Chrome
- 

10 Year Master Handles

- White Black Grey
- Satin Chrome Gold

Midrail

- 68mm slimline 110mm letterplate

Height from base of cill _____

Letterplate

- White Black Gold Satin Chrome

French Doors Only (Fingerbolts fitted on slave)

- Master handle** Left door Right door
- 1 handle set

Cill requirements included in overall frame height

- 94mm 149mm 173mm No cill required

Note: Cill platform height is 25mm