

TRIPLE TRACK KAWNEER ALUMINIUM INLINE PATIO DOOR QUOTE/ORDER FORM

TRADE
ORDER FORM
JUNE 2018
V1.JUNE18

Enquiry please quote

Order please process

Contact Details

Ordered By _____

Company Name _____

Address _____

Postcode _____

Tel _____

Email _____

Order No. _____

Your Reference _____

Delivery Date Requested _____

Site Contact

Company Name _____

Delivery Address _____

Postcode _____

Tel _____

Sash - 82mm standard

Outerframe

Outerframes delivered in kit form and must be assembled and sealed on site. Two tubes of sealant come with each door kit.

Overall frame width (mm) _____

Overall frame height (mm) _____

If 6m wide or 2.2m high sashes will be delivered in kit form

Cill requirements (25mm to be included in overall frame height)

141mm 196mm 236mm No cill required

24mm Add on to head Yes No

34mm Add on to head (for night vents) Yes No

L R T B

Glazing – square bead

Glazed Unglazed

28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer

28mm 32mm 36mm

Door has to comply with Document Q of the Building Regulations (additional costs apply for the PAS 24:2016 specification product)

Keyed Alike (on multiple frames only)

Date Of Order _____ Date Required _____

Door will be fitted in:

Sheltered location Exposed location

Stock Colours on a 2 week lead time

RAL 7016 Textured Anthracite Grey RAL 9016 Textured White

RAL 7016 Anthracite Grey Matt RAL 9016 White Gloss

RAL 7016 Textured Anthracite Grey outside / RAL 9016 Textured White inside

RAL 7016 Anthracite Grey Matt outside / RAL 9016 Traffic White inside

Available on a 3 week lead time

RAL 9005 Textured Jet Black RAL 7035 Textured Light Grey

RAL 7015 Textured Slate Grey

Other RAL Colour on a 5-6 week lead time: _____

Marine Grade Finish Yes No

Note: Mandatory within 500 metres of the sea, tidal estuary or in a swimming pool or any other chemical or industrial environment

Drainage required Yes No

Sliding panel – internal standard. Tick box for external slider

Handle – Standard specification

400mm cranked brushed stainless bar handle to inside, Bathroom actuator, 4 mushroom lock with central hook, multiple keeps. Euro cylinder escutcheon inside.

Optional:

Full cylinder (to unlock from outside)

400mm cranked bar handle to outside (to match internal)

Midrail 68mm 78mm

Midrail height (from base of frame to centre of midrail) _____ mm

Night Vent (1 x 5000mm² IN + 34mm double add on supplied)

Black White Grey

Configuration – viewed from outside








Please indicate below: fixed panel/s and direction of travel when viewed from outside.

3 pane 6 pane X = slider O = fixed panel

AA4110 Slide & Lift/slide profiles and accessories.











Sliding sash profiles



Interlock profiles































Isolator profiles

Glazing gaskets



Kawneer's continuous development and engineering programmes may bring about product changes. Kawneer reserve the right to introduce without notice such changes which will not detract from the product's performance.

Copyright in this drawing or the drawing is reserved by Kawneer, whose prior written consent is required for its use, reproduction or for publication to any third party. All other rights reserved. Subject to modifications.



A SUPERIOR ANIMAL ALTOGETHER.

