

# TRIPLE TRACK KAWNEER ALUMINIUM LIFT AND SLIDE PATIO DOOR QUOTE/ORDER FORM

TRADE  
**ENQUIRY/ORDER FORM**  
JUNE 2018  
V5.JUNE18

**Enquiry** please quote

**Order** please process

## Contact Details

Ordered By \_\_\_\_\_

Company Name \_\_\_\_\_

Address \_\_\_\_\_

Postcode \_\_\_\_\_

Tel \_\_\_\_\_

Email \_\_\_\_\_

Order No. \_\_\_\_\_

Your Reference \_\_\_\_\_

Delivery Date Requested \_\_\_\_\_

## Site Contact

Company Name \_\_\_\_\_

Delivery Address \_\_\_\_\_

Postcode \_\_\_\_\_

Tel \_\_\_\_\_

Sash - 102mm meeting style

## Outerframe

Outerframes delivered in kit form and must be assembled and sealed on site. Two tubes of sealant come with each door kit.

Overall frame width (mm) \_\_\_\_\_

Overall frame height (mm) \_\_\_\_\_

If 6m wide or 2.2m high sashes will be delivered in kit form

## Cill requirements (25mm included in overall frame height)

Frame extension to head

141mm      249mm      289mm      No cill required

24mm Add on to head      Yes      No

34mm Add on to head (for night vents)      Yes      No

L      R      T      B

## Glazing – square bead

Glazed      Unglazed  
28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer

28mm      32mm      36mm

Door has to comply with Document Q of the building Regulations  
(additional costs apply for the PAS 24:2016 specification product)

**Keyed Alike - multiple frames only**

Date Of Order \_\_\_\_\_ Date Required \_\_\_\_\_

## Door will be fitted in:

Sheltered location      Exposed location

## Stock Colours on a 2 week lead time

RAL 7016 Textured Anthracite Grey      RAL 9016 Textured White

RAL 7016 Anthracite Grey Matt      RAL 9016 White Gloss

RAL 7016 Textured Anthracite Grey outside / RAL 9016 Textured White inside

RAL 7016 Anthracite Grey Matt outside / RAL 9016 Traffic White inside

## Available on a 3 week lead time

RAL 9005 Textured Jet Black      RAL 7035 Textured Light Grey

RAL 7015 Textured Slate Grey

Other RAL Colour on a 5-6 week lead time: \_\_\_\_\_

Marine Grade Finish      Yes      No

Note: Mandatory within 500 metres of the sea, tidal estuary or in a swimming pool or any other chemical or industrial environment

Drainage      Yes      No

Sliding panel – internal standard. Tick box for external slider

## Handles – Brushed stainless handle inside and out

No lever handle externally      Finger pull externally

Midrail      68mm      78mm

Midrail height (from base of frame to centre of midrail) \_\_\_\_\_ mm

## Night Vent (1 x 5000mm<sup>2</sup> IN + 34mm double add on)

Black      White      Grey

## Configuration – viewed from outside

Please indicate below: fixed panel/s and direction of travel when viewed from outside. X = slider O = fixed panel

3 panes      6 panes