



Mayfair Elegance Sash Windows

Order form
June 2016

Enquiry please quote Order please process

Contact details

Company name _____

Delivery address _____

_____ Postcode _____

Reference _____

Requested delivery date _____

Telephone _____

Fax _____

Email _____

Ordered by _____

Mayfair specification

White Foil both sides. Black gasket on bead.

Mechanically jointed outerframe, sash and deep bottom rail

Run-through horns

Internal Georgian bar – fluted authentic

External Georgian bar - puttyline

White spacer bar. Grey woolpile.

KAT bespoke 'Hook and Claw' cam catches

146mm outerframe

Hardware

White (standard) Satin

Chrome Pewter Antique gold

Window has to comply with Document Q of the Building Regulations (additional costs apply for the SBD specification product)

No. of windows					
Reference					
Total width		mm	mm	mm	mm
Total height		mm	mm	mm	mm
Transom drop					
Fire Egress?	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Opening restrictor	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Tilt facility	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> F
Night vent required	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
Night vent Location	<input type="checkbox"/> Top sash 2/4000mm ² <input type="checkbox"/> Add-on 5000mm ²	<input type="checkbox"/> Top sash 2/4000mm ² <input type="checkbox"/> Add-on 5000mm ²	<input type="checkbox"/> Top sash 2/4000mm ² <input type="checkbox"/> Add-on 5000mm ²	<input type="checkbox"/> Top sash 2/4000mm ² <input type="checkbox"/> Add-on 5000mm ²	<input type="checkbox"/> Top sash 2/4000mm ² <input type="checkbox"/> Add-on 5000mm ²
W.E.R. Rating	<input type="checkbox"/> A <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> C	<input type="checkbox"/> A <input type="checkbox"/> C
Georgian bar type	<input type="checkbox"/> Authentic <input type="checkbox"/> Glazed in	<input type="checkbox"/> Authentic <input type="checkbox"/> Glazed in	<input type="checkbox"/> Authentic <input type="checkbox"/> Glazed in	<input type="checkbox"/> Authentic <input type="checkbox"/> Glazed in	<input type="checkbox"/> Authentic <input type="checkbox"/> Glazed in
Outside sketch Please sketch in any Georgian bar or glass requirements T = Toughened Glass L = Laminated O = Obscure (Please provide Pattern) Obscure Pattern =					
Extra cill (welded?)	@ mm	@ mm	@ mm	@ mm	@ mm
Coupler	mm	mm	mm	mm	mm
Frame extension	@ mm	@ mm	@ mm	@ mm	@ mm
Bay assembly	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135	<input type="checkbox"/> 90 <input type="checkbox"/> 120 <input type="checkbox"/> 135
Fixing lugs	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No

Additional requirements:

Your Details - please provide us with complete and accurate information to allow rapid order processing - including full delivery address, especially if different from your office/factory address. Request the date windows are required (Std. lead time is 2-3 weeks) we will confirm delivery date by fax. Include your contact details (Placed By) in case we need to clarify anything on your order, and please give orders a clear order reference - preferably with your purchase order number for maximum traceability and quick easy invoicing.

Window Details

NB: Please order windows in same room/elevation together to help us match specification/style. Some windows may require large/large sash combination due to size - standard is large/small sashes.

- 1 Outerframe Depth** - The 146mm frame is ovolo moulded on both the internal and external faces. The integral cill is 146mm.
- 2 Deep Bottom Rail** - A mechanically jointed aesthetic rail to replicate traditional sightlines - bottom sash base rail is 105mm in height.
- 3 Gasket Colour** - Mayfair Elegance VS have lowline gaskets in black.
- 4 Hardware** - KAT sash windows are manufactured with a full suite of bespoke matching window hardware, with white fitted as standard. We also have available hardware finished in bright chrome, satin, antique gold, or antique pewter.
- 5 Key Locking** - For extra security locking hook and claw cam catches are fitted as standard with allen key locking.
- 6 Number of Windows** - If you wish to order multiple windows of identical size and specification state required quantity.
- 7 Reference** - This offers the opportunity to reference your windows individually for easy identification on site (Lounge, bedroom, etc.) and your reference will be displayed on frame labels.
- 8 Total Width** - Please state the total overall finished window width including any extras or frame extenders, etc. Allow 10mm tolerance.
- 9 Total Height** - Please state the total overall finished window height including any extra cills or frame extenders, etc. Allow 10mm tolerance.
- 10 Transom Drop** - Please state the dimension from the top of the outerframe to the central meeting point of the sashes, if left blank standard is half the height of the window - but we can cater for most requirements (1/3rd - 2/3rds or 2/5ths - 3/5ths etc.).
- 11 Fire Escape?** - If the window needs to meet Part B fire egress requirements let us know! Please note minimum sizes apply (KAT will confirm compliance) and where this option is selected hardware configuration should be checked with local planning department. KAT have special Fire Egress windows available (at an extra charge) to allow smaller frames to comply with Building Regulations.
- 12 Opening Restrictors** - Primarily a child safety feature, these bespoke fixtures limit the sash opening - available in white, gold, bright chrome, antique pewter, satin and legrand gold.
- 13 Tilt Facility** - 'No' = Standard sashes will slide up and down only, 'Yes' = optional 'easy clean' tilt facility available to facilitate cleaning from inside + extra ventilation etc. - 2 tilt restrictor arms are fitted to all tilting sashes, 'F' = a totally fixed window (both sashes).

- 14 Vent Required** - night vents are available fitted through either the head of the top sash or alternatively through a 30mm or 50mm add-on to the head of the outerframe (please specify which option you require, 'Sash' or 'ADD-ON').
- 15 W.E.R. Rating** - Select the BFRC approved window energy rating required. All frames with standard 4-16-4 glass configuration will be supplied 'C' rated as standard.
- 16 Outside Sketch** - All KAT VS are fully glazed with 4-16-4 clear Planitherm Total + low 'e' glass as standard, for any additional glazing requirements e.g. toughened/Laminated mark the window drawings with 'T' or 'L' as applicable, for obscure glass 'O' please confirm desired pattern.
- 17 Extra Cill** - 85mm, 120mm & 160mm cills available to go under the frame, 160mm can be welded for bays. Specify which cill and overall size, if cill horns/over length cills are required.
- 18 Coupler** - A 2mm PVCu 'H' section trim is available for fixing multiple frames together, they also require screw fixing. As standard, Mayfair Elegance coupled windows will be supplied separately to be joined on site, for ease of installation.
- 19 Frame Extension** - 15mm, 30mm & 50mm add-ons available to build up frame - 55mm depth, ideal for check reveals. Specify which add-on and required size/quantity (2 no. required to build up front and back).
- 20 Bay Assembly** - A non-structural non-foiled baypole is available in 90°, 120° or 135° fixed angles. A variable bay pole assembly will be supplied with foiled products. Please sketch bays on additional sheets.
- 21 Fixing Lugs** - To assist with quick, easy, high quality installation stainless steel fixing lugs are available, 'yes' = 6 supplied per window.

Additional Requirements:

Please include details of any special requirements in space provided or on supplementary sheets, e.g. drawings of bays, etc. If your sash window needs to comply with a particular W.E.R. rating please let us know, we will try to oblige.

If you are planning to install KAT sash windows in a severe weather facing location, please contact the sales office for advice.

Bays, Welded Cills and Arched Windows

A separate order form is available for arched windows, please enquire - please also sketch any bay layouts on additional sheets.

Window has to comply with Document Q of the Building Regulations (additional costs apply for the SBD specification product)

NB: Please give finished internal facet sizes and required angles for any bay window assemblies.