

# TRIPLE TRACK KAWNEER ALUMINIUM LIFT AND SLIDE HIGH PERFORMANCE PATIO DOOR AA3572

## QUOTE/ORDER FORM

TRADE  
ENQUIRY/ORDER FORM  
NOV 2018

Enquiry please quote  Order please process

Date Of Order \_\_\_\_\_ Date Required \_\_\_\_\_

### Contact Details

Ordered By \_\_\_\_\_

Company Name \_\_\_\_\_

Address \_\_\_\_\_

Postcode \_\_\_\_\_

Tel \_\_\_\_\_

Email \_\_\_\_\_

Order No. \_\_\_\_\_

Your Reference \_\_\_\_\_

Delivery Date Requested \_\_\_\_\_

### Site Contact

Company Name \_\_\_\_\_

Delivery Address \_\_\_\_\_

Postcode \_\_\_\_\_

Tel \_\_\_\_\_

### Sash

74mm meeting style (can meet PAS 24)

100mm meeting style

### Outerframe

Outerframes delivered in kit form and must be assembled and sealed on site. Two tubes of sealant come with each door kit.

Overall frame width (mm) \_\_\_\_\_

Overall frame height (mm)

If 6m wide or 2.2m high sashes will be delivered in kit form. Sashes can be made up to 3m x 3m. Subject to max sash weight 400kgs.

Cill requirements (25mm to be included in overall frame height)

Frame extension to head

250mm stub cill  290mm  No cill required

24mm Add on to head  Yes  No

34mm Add on to head (for night vents)  Yes  No

L  R  T  B

### Glazing – square bead

Glazed  Unglazed

28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer

28mm (U value 1.3)  36mm (U value 1.0–1.1)  56mm

Door has to comply with Document Q of the building Regulations (additional costs apply for the PAS 24:2016 specification product).

Keyed Alike – multiple frames only

Door will be fitted in:

Sheltered location  Exposed location

### Stock Colour

RAL 7016 Textured Anthracite Grey

### Available on a longer lead time

RAL 7015 Textured Slate Grey  RAL 7016 Anthracite Grey Matt

RAL 7035 Textured Light Grey  RAL 9016 White Gloss

RAL 9005 Textured Black  RAL 9016 Textured White

RAL 7016 Textured Anthracite Grey outside/ RAL 9016 Textured White inside

RAL 7016 Anthracite Grey Matt outside/ RAL 9016 Traffic White Gloss inside

### Other RAL Colour

Marine Grade Finish  Yes  No

Mandatory within 500 metres of the sea, tidal estuary or in a swimming pool or any other chemical or industrial environment.

Drainage  Yes  No

Sliding panel – internal standard. Tick box for external slider

### Handle – Standard specification

Brushed Stainless handle inside and out

### Optional:

No lever handle externally

Finger pull externally

Night ventilation lock

Night Vent (1 x 5000mm<sup>2</sup> IN + 34mm double add on)

Black  White  Grey

### Configuration – viewed from outside

Please indicate below: fixed panel/s and direction of travel when viewed from outside. X = slider O = fixed panel

3 panes  6 panes