

TRIPLE TRACK KAWNEER ALUMINIUM LIFT AND
SLIDE HIGH PERFORMANCE PATIO DOOR AA3572

QUOTE/ORDER FORM

TRADE
ENQUIRY/ORDER FORM
MAR 2019

Enquiry please quote

Order please process

Date Of Order _____ **Date Required** _____

Contact Details

Ordered By _____

Company Name _____

Address _____

_____ **Postcode** _____

Tel _____

Email _____

Order No. _____

Your Reference _____

Delivery Date Requested _____

Site Contact

Company Name _____

Delivery Address _____

_____ **Postcode** _____

Tel _____

Sash

74mm meeting style (can meet PAS 24)

100mm meeting style

Outerframe

Outerframes delivered in kit form and must be assembled and sealed on site. Two tubes of sealant come with each door kit.

Overall frame width (mm) _____

Overall frame height (mm)

If 6m wide or 2.2m high sashes will be delivered in kit form. Sashes can be made up to 3m x 3m. Subject to max sash weight 400kgs.

Cill requirements (25mm to be included in overall frame height)

Frame extension to head

250mm stub cill 290mm No cill required

24mm Add on to head Yes No

34mm Add on to head (for night vents) Yes No

L R T B

Glazing – square bead

Glazed Unglazed

28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer

28mm (U value 1.3) 36mm (U value 1.0–1.1) 56mm

Keyed Alike – multiple frames only

Door will be fitted in:

Sheltered location Exposed location

Stock Colour

RAL 7016 Textured Anthracite Grey

Available on a longer lead time

RAL 7015 Textured Slate Grey RAL 7016 Anthracite Grey Matt

RAL 7035 Textured Light Grey RAL 9016 White Gloss

RAL 9005 Textured Black RAL 9016 Textured White

RAL 7016 Textured Anthracite Grey outside/ RAL 9016 Textured White inside

RAL 7016 Anthracite Grey Matt outside/ RAL 9016 Traffic White Gloss inside

Other RAL Colour _____

Marine Grade Finish Yes No

Mandatory within 500 metres of the sea, tidal estuary or in a swimming pool or any other chemical or industrial environment.

Drainage Yes No

Sliding panel – internal standard. Tick box for external slider

Handle – Standard specification

Brushed Stainless handle inside and out

Optional:

No lever handle externally

Finger pull externally

Night ventilation lock

Night Vent (1 x 5000mm² IN + 34mm double add on)

Black White Grey

Configuration – viewed from outside

Please indicate below: fixed panel/s and direction of travel when viewed from outside. X = slider O = fixed panel

3 panes 6 panes

