

TWIN TRACK KAWNEER ALUMINIUM LIFT AND SLIDE  
HIGH PERFORMANCE PATIO DOOR AA3572

**QUOTE/ORDER FORM**

TRADE  
**ENQUIRY/ORDER FORM**  
MAR 2019

**Enquiry** please quote

**Order** please process

**Date Of Order** \_\_\_\_\_ **Date Required** \_\_\_\_\_

**Contact Details**

**Ordered By** \_\_\_\_\_

**Company Name** \_\_\_\_\_

**Address** \_\_\_\_\_

\_\_\_\_\_ **Postcode** \_\_\_\_\_

**Tel** \_\_\_\_\_

**Email** \_\_\_\_\_

**Order No.** \_\_\_\_\_

**Your Reference** \_\_\_\_\_

**Delivery Date Requested** \_\_\_\_\_

**Site Contact**

**Company Name** \_\_\_\_\_

**Delivery Address** \_\_\_\_\_

\_\_\_\_\_ **Postcode** \_\_\_\_\_

**Tel** \_\_\_\_\_

**Sash**

74mm meeting style (can meet PAS 24)

100mm meeting style

**Outerframe**

Outerframes delivered in kit form and must be assembled and sealed on site. Two tubes of sealant come with each door kit.

**Overall frame width** (mm) \_\_\_\_\_

**Overall frame height** (mm)

If 6m wide or 2.2m high sashes will be delivered in kit form. Sashes can be made up to 3m x 3m. Subject to max sash weight 400kgs.

**Cill requirements** (25mm to be included in overall frame height)

Frame extension to head

190mm stub cill      250mm      No cill required

**24mm Add on to head**      Yes      No

**34mm Add on to head (for night vents)**      Yes      No

L      R      T      B

**Glazing – square bead**

Glazed      Unglazed

28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer

28mm (U value 1.3)      32mm (U value 1.0–1.1)      56mm

**Keyed Alike** – multiple frames only

**Door will be fitted in:**

Sheltered location      Exposed location

**Stock Colour**

RAL 7016 Textured Anthracite Grey

**Available on a longer lead time**

RAL 7015 Textured Slate Grey      RAL 7016 Anthracite Grey Matt

RAL 7035 Textured Light Grey      RAL 9016 White Gloss

RAL 9005 Textured Black      RAL 9016 Textured White

RAL 7016 Textured Anthracite Grey outside/ RAL 9016 Textured White inside

RAL 7016 Anthracite Grey Matt outside/ RAL 9016 Traffic White Gloss inside

**Other RAL Colour** \_\_\_\_\_

**Marine Grade Finish**      Yes      No

Mandatory within 500 metres of the sea, tidal estuary or in a swimming pool or any other chemical or industrial environment.

**Drainage**      Yes      No

**Sliding panel** – internal standard. Tick box for external slider

**Handle – Standard specification**

Brushed Stainless handle inside and out

**Optional:**

No lever handle externally

Finger pull externally

Night ventilation lock

**Night Vent** (1 x 5000mm<sup>2</sup> IN + 34mm double add on)

Black      White      Grey

**Configuration – viewed from outside**

Please indicate below: fixed panel/s and direction of travel when viewed from outside. X = slider O = fixed panel

2 sashes      3 sashes      4 sashes