

Customer name:	QUOTE ONLY: <input type="checkbox"/>	ORDER <input type="checkbox"/> JOB NO. <input style="width:100%;" type="text"/>	I will accept delivery:
Address:	NO: <input style="width:100%;" type="text"/>	Collection date required <input style="width:100%;" type="text"/>	Delivery date reqd:
Telephone:	IMPORTANT: PLEASE READ CAREFULLY AND SIGN BELOW FOR ORDERS:		Approx. time:
YOUR reference:	Signed: _____		Delivery address:
YOUR order number:	Print name: _____	Date: _____	Postcode:
Trade card number:			Contact tel no.:

Inline Sliding Lift & Slide Please note lead time on Lift & Slide door sets is on application

Overall Width (mm) Overall Height (mm)

Including Cills & Add Ons

Duo-Rail

Tri-Rail

Please Indicate:
Slider 'X'
Fixed 'O'
Direction '← / →'

--	--	--	--	--	--

All viewed from the outside - Please indicate master door if applicable

STANDARD SINGLE COLOUR OPTIONS:

RAL 9005 Black Matt

RAL 7016 Anthracite Grey Matt

RAL 9910 White High Gloss

STANDARD DUAL COLOUR:

RAL 7016 Anthracite Grey Matt Externally / RAL 9910 White High Gloss Internally

***RAL INTERNALLY:**

COLOUR:

HIGH GLOSS SEMI GLOSS MATT

***RAL EXTERNALLY:**

COLOUR:

HIGH GLOSS SEMI GLOSS MATT

Marine Guarantee Required Please Tick *For Marine Environment applications, please refer to disclaimer at foot of page

Any of the above will incur an additional set-up cost and extended lead time

Cill: No Cill 177mm Cill Horns: mm (*No Horns as Standard*)

No Cill available on a Tri-rail/All items will be Face Drained

Trickle Vent: Qty (4000m² through 22mm Patio Extension to the head)

Door Handle: White Black Silver

28mm Glazed: Yes No (Standard 28mm glazing comprising of 4mm Tough K Softcoat + ARGON + 4 Tough Optiwhite Swiss Black Spacer Bar)

ADDITIONAL REQUIREMENTS:

Please Note: We cannot guarantee any product installed within 50 metres of the coast, source of pollution or 2 metres from a swimming pool against deterioration of profile or hardware. Any product fitted within 5000 metres of a hostile environment, a recommended cleaning regime must be adhered to and recorded (please consult product guide) - Additional costs may be incurred, please advise on the environment if appropriate. All frames are non-load bearing. Sliding pane to the inside. Door stop black as standard.

Size Limitations: Each panel being no larger than 2000mm wide with a maximum height of up to 3000mm, subject to wind load deflection. Maximum 200kgs per sash.