The K64 Collection



Customer:							Date:							
Reference:						Contact Email:								
Delivery Address & Postcode:							Contact Number	er:						
Door Model:							Model Type:							
Exterior Colour:							Interior Colour:							
Open In Open Out							F	Hinge Left		Hinge Right		Right		
Rain Deflector available on a select number of models; recomm				ended	nded for inward opening doors			Black		Anodised Silver				
Black protective aluminium edge trim cover internally Black Hook Bolt and strike plate (Steel finish as standard)														
All Doors Viewed Externally														
	Total Wid	tal Width:			Tota	l Height:	mm		Dimensions include any		/ add-ons			
	Side light	s Left		mm	Doo	r Width	n	nm :	Side	lights Right		mm	Add on Top	
Add on Left	Top Light		Width			mm	Top Light			Height		mm	Add on Right	
1 x 28mm	•	↑ 1 x 28mm ## ################################									1 x 28mm			
Hinges	Black	S	Silver	Go	old	150mm Cill ((25mm)			Silver Anodised			Black	
					G	lazing Sp	ecification	S						
Triple Glazing in Door		Clear	Black	Opaque			eflex Bronze	Relfe	ex Gr	rey Sandblasted	\	/enetian N	Mirror (non-standard)	
Triple Glazing in Side	Lights	Same	as Door	Other [Desigr	١	Triple Gla	azing i	in To	p Light Same as	s Doc	or Oth	er	
Décor on the door		lnox		Black		Glass (a	vailability subject	to mo	del)					
External Handle Options Lever Handle fitted internally as standard in same colour as external pullbar Loc									Lock					
Round Pull Bar	600mm		1200mm		1800mm		Black		Steel			Additional deadbolt locking		
Square Pull Bar		600mm 1200mr					Black		Steel			point towards top of door and escutcheon		
Lever handle Internal Lever Handle		Black Silver Black Silver			Gold Gold							Manual Day Latch		
Internal Ecver Flandic	Diac		Olive			doid					L			
Optional Extras Comm					omments									
5 Keys (3 supplied as standard)														
Letterbox Black White Gold Anodised														
Thumbturn Cylinder Internally Silver Black Gold														
Spyhole Black Steel														
	1,0000 0000	door sash. 65	mm doon fro	ma Maat	~ DC0	and DAC			-					

Standard Specification: 64mm deep door sash, 65mm deep frame. Meets RC2 and PA 24 security. 0.77 W/m2K U Value on Solid Designs, 0.88 W/m2K on Glazed Designs. Multi-point lock with two hooks, two horizontal bolts, one deadbolt and a latch. 20mm Warm Aluminium low threshold. 4 Hinge security dog bolts. 15.5mm hinge clearance. Doors weigh circa 90 Kgs

Minimum Size – Single Door: 778mm wide x 1806mm high Maximum Size – Single Door: 1148mm wide x 2246mm high Subject to certain model limitations – please ask our Customer Service Team for details

Signature:	

By signing this document, I understand that my order will be processed as per the contents of this form. Please be aware KAT UK are not responsible for any errors or omissions.

If you wish to change the specifications or anything is unclear, please do not sign this document and email us with any required amendments.