

# ALUMINIUM BIFOLDING DOORS



KAT UK's aluminium bifold doors are suitable for use in a residential or commercial property and are available in a wide range of RAL colours, including a dual colour option.

## Features:

- Quick glaze bead
- U Value 1.5 W/m<sup>2</sup>K with a 1.0 W/m<sup>2</sup>K centre pane
- Anthracite Grey, Traffic White or Jet Black as standard
- Dual colour - Anthracite Grey outside, Traffic White inside
- Wide choice of opening configurations
- Option to incorporate a lead traffic door for easy access
- Handles available in seven colour finishes
- Open outwards
- Fully Document L Compliant
- EPDM high quality gaskets for enhanced weather protection
- Multi-point locking on lead door
- Shoot-bolt locking on intermediate sashes
- Weathered standard threshold



## Options:

- Upgrade to PAS 24:2016 available
- Dual colour options
- Metallic and wood effect finishes
- Low threshold
- Cill sizes 85mm Stub, 150mm, 190mm, 225mm, Integrated cill option
- Trickle vents fitted in 42mm Add-on to head
- 20mm or 42mm Add-on

## Dimensions:

- Minimum sash width 700mm
- Maximum sash width 1200mm
- Maximum sash height 2500mm
- Maximum sash weight 100kg
- Frame depth 70mm
- Interlock sightline 122mm

## Handles:

Available in Anthracite, White, Gold, Stainless Steel, Black, Chrome or Rose Gold



**Note:** Black intermediate handles and hinges as standard

Toe and heeling adjusting tool supplied as standard for easy toe and heeling

01625 439666

w: [katuk.co.uk](http://katuk.co.uk) | e: [enquiries@katuk.co.uk](mailto:enquiries@katuk.co.uk)

